



KEMENTERIAN AGAMA
FAKULTAS ILMU TARBİYAH DAN KEGURUAN
UNIVERSITAS ISLAM NEGERI MAULANA MALIK IBRAHIM MALANG
Jl. Gajayana No. 50 Telp. (0341) 552398, Fax. 552398 Malang Kode Pos 65144
Website: www.fitk.uin-malang.ac.id Email: fitk_uin_maliki@yahoo.com

Nomor : Un.3.1/KS.01.7/ 572 /2014
Lampiran : 1 (satu) bendel
Perihal : **Permintaan Informasi Harga Barang**

20 Oktober 2014

Yth. _____
Di Tempat

Assalamua'laikum wa Rahmatullah wa Barakatuh

Sehubungan rencana realisasi pelaksanaan pekerjaan **Belanja Modal Peralatan dan mesin berupa paket sound system auditorium untuk Fakultas Ilmu Tarbiyah dan Keguruan UIN Maulana Malik Ibrahim Malang**, bersama ini kami bermaksud agar perusahaan Saudara memberikan informasi tentang harga barang sesuai dengan Rencana Anggaran Biaya (RAB) yang kami lampirkan dalam surat ini.

Apabila informasi harga yang Saudara berikan sesuai dan kami nilai wajar, maka kami akan memberi kesempatan perusahaan Saudara untuk membuat penawaran terhadap pekerjaan tersebut.

Kami harap data barang dan harganya dapat kami terima paling lambat pada :

hari, tanggal : Senin, 27 Oktober 2014
waktu : 14.00 WIB
tempat : Fakultas Ilmu Tarbiyah dan Keguruan UIN Maulana Malik Ibrahim Malang
: Atau penawarannya bisa dikirim via e-mail ke : ulp@uin-malang.ac.id
atau ulp_uinmalang@kemenag.go.id atau fitk_uin_maliki@yahoo.com
Telp. Fak. Ilmu Tarbiyah dan Keguruan 0341-552398

Surat tentang informasi harga barang tersebut, ditujukan:

Kepada Yth:

*Pejabat Pembuat Komitmen Fakultas Ilmu Tarbiyah dan Keguruan
Universitas Islam Negeri Maulana Malik Ibrahim Malang Jl. Gajayana No. 50 Malang.*

Demikian, atas perhatian dan kehadiran bapak/ibu disampaikan terima kasih.

Wassalamua'laikum wa Rahmatullah wa Barakatuh

Pejabat Pembuat Komitmen,

Dr. H. Wahidmurni, M.Pd
NIP. 19690303 200003 1 002

Lampiran : Surat Pejabat Pembuat Komitmen
 Nomor : Un.3.1/KS.01.7/ 572 /2014
 Tanggal : 20 Oktober 2014
 Tentang : Permintaan Informasi Harga Barang

Pekerjaan : **Belanja Modal Peralatan dan mesin berupa paket sound system auditorium untuk Fakultas Ilmu Tarbiyah dan Keguruan UIN Maulana Malik Ibrahim Malang**
 Lokasi : **Fakultas Ilmu Tarbiyah dan Keguruan UIN Maulana Malik Ibrahim Malang**
 Tahun Anggaran : **2014**

NO	NAMA BARANG	SPESIFIKASI	QTY	HARGA SATUAN (Rp)	JUMLAH (Rp)
1	Paket sound system auditorium	<p>Kelengkapan Paket :</p> <ul style="list-style-type: none"> - 2 Unit : Speaker Pasif - 2 Unit : Subwoofer Pasif - 2 Unit : Mic wired - 1 Unit : Mixer - 1 Unit : Digital Equalizer - 2 Unit : Power Amplifier - 2 Unit : stand speaker - 1 Unit : Rack Case (untuk PA, DE) - 1 Lot : Kabel Mic & Kabel Speaker (untuk semua perangkat dalam paket) - Setup / instalasi <p>Spesifikasi Unit</p> <p>1. SPEAKER PASSIVE</p> <ul style="list-style-type: none"> • Passive 15" loudspeaker with 600 watt power rating at 8 ohms • High frequency dispersion is 90 x 50 degrees, ideal for L/R speaker configurations • Maximum SPL of 128dB • Designed for use as either a floor monitor or as a pole-mounted main speaker • DuraFlex enclosure finish protects the cabinet • 16 gauge steel grill protects the drivers • SonicGuard technology protects the HF driver from excessive power • 12 x M10 suspension points • Dimensions (H x W x D) 650 mm x 429 mm x 457 mm ,Net Weight 21 kg/46 lbs. <p>2. SUBWOOFER PASSIVE</p> <ul style="list-style-type: none"> • Passive 18" subwoofer with 1,600-watt RMS power rating at 8 ohms • Maximum SPL of 130dB • Low-frequency range extends down to 35Hz for incredibly rich bass response • DuraFlex enclosure finish protects the cabinet • 16 gauge steel grill protects the drivers • Dimensions (H x W x D) 678 mm x 536 mm x 615 mm , Net Weight 36 kg 79 lbs. 	1 paket		

NO	NAMA BARANG	SPESIFIKASI	QTY	HARGA SATUAN (Rp)	JUMLAH (Rp)
		<p>3. ANALOG MIXING CONSOLE</p> <ul style="list-style-type: none"> • Professional 16-channel 4-bus mixer with onboard effects and USB I/O • 10 low-noise, high-headroom Mackie mic preamps with +50dB gain range • Dedicated inline compression for critical inputs (ch. 5-8) • 32-bit RMFX processor with 16 "Gig-Ready" reverbs, choruses and delays • Precision 7-band graphic EQ for tuning mains and monitors • USB I/O for recording shows and music playback via Mac or PC • Stream subgroups 1-2 or main L/R to your computer for recording • Stereo USB/tape I/O with input level control to mains • Convenient USB return to stereo channel for implementation of EQ, auxes and more • 3-band EQ with sweepable midrange on mono channels • 16 high-headroom line inputs (8 mono, 4 stereo) • Individual channel mute switches and overload (OL) indicators • 18dB/octave 100Hz low cut filters on all mic channels • Inserts on mono mic/line channels (ch. 1-4) for connecting outboard processors • 60mm faders for input channels, subgroups and mains • 48V phantom power with LED for use with condenser mics • FX mute button also controllable via footswitch • Break switch mutes all channels for music playback between sets • Control room / headphone outputs with rotary level control • Balanced XLR and balanced/unbalanced 1/4" main outputs • Rack-mountable design using optional rack ears • Rugged steel chassis • Switching multi-voltage power supply for worldwide use • Includes Tracktion 3 Music Production Software for Mac or PC • Windows: 7 (32/64), Vista (32/64) RTM or XP SP2; Pentium 4, Celeron, or Athlon XP processor; 512MB RAM • Mac: OSX 10.4.11 - 10.6.4; G4 processor; 512MB RAM • Dimension H 3.8" x W 18.7" x D 16" • Weight : 20 lbs (shipping weight) 			

NO	NAMA BARANG	SPESIFIKASI	QTY	HARGA SATUAN (Rp)	JUMLAH (Rp)
		<p>4. MANAGEMENT SPEAKER DIGITAL</p> <ul style="list-style-type: none"> • USB connectivity makes it easy to update speaker and amp settings • Stereo feedback elimination with 12 feedback notch filters • Full-time RTA • Dual 28-band Graphic EQ • Classic dbx compressor • 120A Sub-harmonic synthesizer • 2 x 2, 2 x 3, 2 x 4, 2 x 5, 2 x 6 crossover configurations • Stereo Multi-band Parametric EQ • Stereo Output Limiters • Alignment Delay • Pink Noise Generator • Auto-EQ with 28-Band RTA • JBL speaker and Crown power amp tunings with Setup Wizard • 25 user programs /25 factory programs • 2-channel XLR input and 6-channel XLR output • Front-panel RTA-M XLR input with phantom power • 24-bit ADC/24-bit DAC, >110dB dynamic range • Power on/off mute circuitry • Front-panel mute buttons • TypeIV conversion system • Full graphic LCD display • Dimension : H 1.75" x D 5.75" x W 19" • Weight : 7 lbs <p>5. POWER AMPLIFIER</p> <ul style="list-style-type: none"> •Amplifier Class : H •Output Power (RMS) 8Ohm : 2 x 1100 W •Output Power (RMS) 4Ohm : 2 x 1800 W •Output Power (RMS) 2Ohm : 2 x 2700 W •Output Power (W)(BTL 8Ohm) : 3000 W •Output Power (W)(BTL 4Ohm) : 3800 W •Freq.Response ±1dB : 10 Hz-50 KHz •Slew Rate : 45 •Damping Factor (20Hz-1Khz) : >650 •Voltage Gain : 35 dB •Input Impedance<balance> : 20KOhm •Input Sensitivity : 0.775V/36dB/32dB •Signal Noise Ratio : >103 dB •Protection : Overload Protect, DC Protect, Short Circuit, InRush Audio, Peak Limiter, Soft Start ,High Temperature Protect, HF Protect, Back EMF Protect,etc •Input Connectors : XLR(x2) ¼" Phone TRS(x2) • Input Filter : Sub Woofer-Full Range-Satellite •Output Connectors : Binding Post (x2) Speak On (x2) •Power Supply : 220 Volt 50Hz/60Hz •Net Weight : 42 Kg 			

NO	NAMA BARANG	SPEKIFIKASI	QTY	HARGA SATUAN (Rp)	JUMLAH (Rp)
		<p>6. MIC WIRED</p> <ul style="list-style-type: none"> - Patented laminated Varimotion™ diaphragm high feedback suppression with supercardiod - Dual shock mount of microphone capsule with integrated pop filter - Dimensions / Weight : Length 185 mm ,Diameter 51 mm, Net Weight 320 g. <p>7. CROSSOVER</p> <ul style="list-style-type: none"> • Featuring state-of-the-art Linkwitz-Riley filters with 24 dB/octave • Individual Limiters on each output for optimal loudspeaker protection • Adjustable time delay for phase alignment between drivers • CD horn equalization for constant directivity horn compensation • Absolutely flat summed amplitude response, zero phase difference • "Low Sum" function provides mono output for subwoofer operation • Individual output Gain controls for all bands • Individual output Mute switches for easy band adjustment • Individual Phase reverse switches for instant phase correction • Switchable 25 Hz Low cut filter on each input for low-frequency driver protection • Servo-balanced and gold-plated XLR connectors for all inputs and outputs • Ultra-high precision potentiometers for ultimate accuracy and repeatability • Illuminated switches for secure operation in dark stage environments • Shielded toroidal mains transformer for minimal noise interference • High-quality components and exceptionally rugged construction ensure long life • Dimension : H 1.75" x D 8.5" x W 19", Weight 5.51 lbs 			
Jumlah					
PPN 10 %					
Jumlah Biaya					
Terbilang					

NB :

* Harga sudah termasuk pajak

* Mohon dicantumkan spesifikasi lengkap

Pejabat Pembuat Komitmen,



Dr. H. Wahidmurni, M.Pd
NIP. 19690303 200003 1 002